



SPECIFICATIONS
 Current Rating: 1 Amps
 Dielectric Withstanding: AC 500V
 Operating Temperature: -40°C to +105°C
 Max Processing Temp: 230° for 30~60 seconds
 (260° for 10 seconds)

MATERIAL&FINISH
 Contact: Brass
 Insulator Material: Nylon 6T
 Color: Black
 Finish: Gold Flash Plated Over Nickel

$A = 1.27 * (\text{NO of Space})$
 $B = A + 1.27$

ORDER INFORMATION

Contact No.	Row Type	Contact Type	Contact Plating	Pin Length (mm)	Others
C1270 - A0	B	D	G	A T	0
04<2X2>~100<2X50> ※ 100P=A0	B: Dual Row	D: SMT	T: Tin S: Selective Gold G: Gold Flash A: Gold 5U" B: Gold 10U" C: Gold 15U" D: Gold 30U"	AT<S.M.T.> C=2.85mm D=7.50mm E=3.50mm F=5.00mm	0: No Option T: Tube Packing R: Reel Packing P: PAD+Tube Packing Q: PAD+Reel Packing

玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.

UNIT	SCALE	PART NAME
MM	3:1	1.27X2.54mm PIN HEADER H=2.5mm SMT DUAL ROW (C=2.85 D=7.5 E=3.5 F=5.0)

制表日: 2003/08/19	DRAWING. <i>Jane</i>	APPROVED	APPD.	CKD.	TOLERANCE ± 0.2	PART NO. C1270-XXBDXAT0	REV. A
-----------------	-------------------------	----------	-------	------	--------------------	----------------------------	-----------