



MATERIAL & FINISH
 Insulator: PBT+Glass FIBER(UL94V-0)
 Contact: Phosphor Bronze
 Contact: Gold -Plated Over Nickel
 Temperature Range: -40°C To $+105^{\circ}\text{C}$
SPECIFICATIONS
 Current Rating: 1A AC,DC
 Voltage Rating: 250V AC,DC
 Contact Resistance: $20\text{m}\Omega$ Min
 Insulation Resistance: $1000\text{m}\Omega$ Min
 Withstanding Voltage: 500V AC/Min
 Withstanding Voltage: 500V AC/Min

5321 - XX G0 A T 01

No. of Pins Per Row	Contact Plating	Insulator Material Option	Connector Type
2-50	SN Tin G0 Gold Flash G2 5U*Gold G3 10U*Gold G4 15U*Gold G5 30U*Gold S0 Gold Flash/Tin Standard G0	A BK-PBT B BK-PA66 C BK-PA6T D BK-PA46 F KB-LCP S Special	Y=Y Type T=T Type . . .

Pin Qty	Dim A	Dim B	Pin Qty	Dim A	Dim B
6P	8.00	2.54	30P	23.24	17.78
8P	9.27	3.81	34P	25.78	20.32
10P	10.54	5.08	40P	29.59	24.13
12P	11.81	6.35	44P	32.13	26.67
14P	13.08	7.62	50P	35.94	30.48
16P	14.35	8.89	60P	42.29	36.83
20P	16.89	11.43	68P	47.37	41.91
24P	18.16	12.70	80P	54.99	49.53
26P	20.70	15.24	100P	67.69	62.23

UNLESS OTHERWISE SPECIFIED TOLERANCE
 X : ± 0.3 X° : $\pm 5^{\circ}$
 X.X : ± 0.2 X.X° : $\pm 1^{\circ}$
 X.XX : ± 0.1 X.XX° : $\pm 0.5^{\circ}$

DRAWN NAME: 1.27IDC-NP

SIZE	A4	SCALE	N:1	PROUCT NO.	
REV	A	UNIT	mm	PROJECT	

DRAWN: 曾春明
 DATE: 19/11/11

CHECKED: _____
 DATE: _____

APPROVED: _____
 DATE: _____

PAGE 1/1