

LM39100 Power Supply Module

FEATURES

- LM39100 Power Supply Module
- Input Voltage Range: AC/DC 8V to 16V
- Input Options 1: Screw Terminal Connector
- Input Options 2: AC/DC Adapter Connector
- Output Voltage: 3.3V / 5.0V
- Output Current: Max. 500mA
- Power Indicator LED

APPLICATIONS


- Simple 3.3V / 5.0V Output Linear Regulator
- Provide local on-card regulation.

DESCRIPTION

The LM39100 Power Supply Module is an accessory board that includes an on-board regulator. This regulator is used to provide local on-card regulation.

APPLICATION GUIDE

The LM39100 Power Supply Module includes LM7805RS voltage regulator and LM39100S-3.3, low dropout voltage regulator, providing fixed supply voltages.




ORDERING INFORMATION



Part Number	LM39100-02
Device	LM39100 Power Supply Module
Package	Assembled Module (50mm X 40mm)

LM39100 Power Supply Module

SCHEMATICS



LAYOUT




LM39100 Power Supply Module

PARTS LIST

Name	Description	P/N	Qty.	Distributor
PCB	Printed Circuit Board	FR4 Lead-Free PCB	1	TAEJIN
IC	LM39100RS-3.3	LM39100RS-3.3, TO-252-3L	1	TAEJIN
IC	LM7805RS	LM7805RS, TO-252-3L	1	TAEJIN
Jack	2P / KF301	2P / KF301, 5.08mm	3	Generic
Diode	Standard Recovery Rectifier Diode	1N4007 M7	4	Generic
LED	LED for Power Indicator	Green LED, 3528	2	Generic
Resistor	1.0kΩ Resistor	1.0kΩ 5% Resistor, 1608(0603)	1	Generic
Capacitor	330uF Capacitor	330uF/10V Ceramic Capacitor	1	Generic
Capacitor	10uF Capacitor	10uF/16V Tantal Capacitor	2	Generic
Capacitor	100nF Capacitor	100nF/25V Capacitor, 1608(0603)	3	Generic

SIZE INFORMATION



LM39100 Power Supply Module

PRODUCT IMAGE



I/O PORT CONFIGURATION AND DESCRIPTION



Designator	Port Name	Port Description
1	Input screw terminal connector	AC/DC Input 8V to 16V
2	Input AC/DC adapter connector.	AC/DC Input 8V to 16V
3	Output Connector 1	3.3V Output Connector
4	Output Connector 2	5.0V Output Connector

LM39100 Power Supply Module

REVISION NOTICE

The description in this datasheet is subject to change without any notice to describe its electrical characteristics properly.

FEATURES

- Fixed and adjustable output voltages to 1.24V
- 410mV typical dropout at 1A
Ideal for 3.0V to 2.5V conversion
Ideal for 2.5V to 1.8V or 1.5V conversion
- 1A minimum guaranteed output current
- 1% initial accuracy
- Low ground current
- Current limiting and thermal shutdown
- Reversed-battery protection
- Reversed-leakage protection
- Fast transient response
- Low-profile SOT-223 package
- Moisture Sensitivity Level 3

APPLICATION

- Battery Powered Equipments
- Motherboards and Graphic Cards
- Microprocessor Power Supplies
- Peripheral Cards
- High Efficiency Linear Regulators
- Battery Chargers

DESCRIPTION


The LM39100/1/2 is 1A low-dropout linear voltage regulators that provide low-voltage, high-current output.

The LM39100/1/2 offers extremely low dropout (typically 410mV at 1A) and low ground current (typically 12mA at 1A). The LM39100 is a fixed output regulator offered in the SOT-223 package. The LM39101 and LM39102 are fixed and adjustable regulators, respectively, in SOP-8 and TO-252 Packages.

The LM39100/1/2 is ideal for PC add-in cards that need to convert from standard 5V to 3.3V, 3.3V to 2.5V or 2.5V to 1.8V. A guaranteed maximum dropout voltage of 630mV overall operating conditions allows the LM39100/1/2 to provide 2.5V from a supply as low as 3.13V and 1.8V from a supply as low as 2.43V. The LM39100/1/2 is fully protected with over current limiting, thermal shutdown, and reversed-battery protection. Fixed voltages of 5.0V, 3.3V, 2.5V, 1.8V and 1.5V are available on LM39100/1 with adjustable output voltages to 1.24V on LM39102.

Absolute Maximum Ratings ^(Note 1)

CHARACTERISTIC	SYMBOL	MIN.	MAX.	UNIT
Supply Voltage	V_{IN}	- 0.3	+ 20	V
Enable Voltage	V_{EN}	-	+ 20	V
Output Voltage	V_{OUT}	-0.3	$V_{IN} + 0.3$	V
Lead Temperature (Soldering, 5 sec)	T_{SOL}	-	260	°C
Storage Temperature Range	T_{STG}	-65	+ 150	°C



ORDERING INFORMATION

Device	Package
LM39100S-X.X	SOT-223
LM39100GS-X.X	
LM39100RS-X.X	TO-252 3L
LM39100GRS-X.X	
LM39101RS-X.X	TO-252 5L
LM39101GRS-X.X	
LM39102RS	
LM39102GRS	
LM39101D-X.X	SOP-8
LM39102D	

X.X = Output Voltage = 1.5, 1.8, 2.5, 3.3, 5.0

1A Low-Voltage Low-Dropout Regulator

LM39100/39101/39102

Operating Ratings (Note 2)

CHARACTERISTIC	SYMBOL	MIN.	MAX.	UNIT
Supply Voltage	V_{IN}	+ 2.25	+ 16	V
Enable Voltage	V_{EN}	+ 2.25	+ 16	V
Maximum Power Dissipation	$PD_{(max)}$	(Note 3)	(Note 3)	
Junction Temperature	T_J	-40	+ 125	°C
Package Thermal Resistance	$\theta_{JA-SOT-223}$	115		°C/W
	$\theta_{JA-TO252}$	95		°C/W
	$\theta_{JA-SOP-8}$	130		°C/W


Ordering Information

V_{OUT}	Package	Order No.	Description	Supplied As	Status
1.5 V	SOT-223	LM39100S-1.5V	1A, Fixed	Reel	Active
	SOT-223	LM39100GS-1.5V	1A, Fixed	Reel	Contact us
	TO-252 3L	LM39100RS-1.5V	1A, Fixed	Reel	Active
	TO-252 3L	LM39100GRS-1.5V	1A, Fixed	Reel	Active
	TO-252 5L	LM39101RS-1.5V	1A, Fixed, Enable	Reel	Active
	TO-252 5L	LM39101GRS-1.5V	1A, Fixed, Enable	Reel	Active
	SOP-8	LM39101D-1.5V	1A, Fixed, Enable	Reel	Active
1.8 V	SOT-223	LM39100S-1.8V	1A, Fixed	Reel	Active
	SOT-223	LM39100GS-1.8V	1A, Fixed	Reel	Contact us
	TO-252 3L	LM39100RS-1.8V	1A, Fixed	Reel	Active
	TO-252 3L	LM39100GRS-1.8V	1A, Fixed	Reel	Active
	TO-252 5L	LM39101RS-1.8V	1A, Fixed, Enable	Reel	Active
	TO-252 5L	LM39101GRS-1.8V	1A, Fixed, Enable	Reel	Active
	SOP-8	LM39101D-1.8V	1A, Fixed, Enable	Reel	Active
2.5 V	SOT-223	LM39100S-2.5V	1A, Fixed	Reel	Active
	SOT-223	LM39100GS-2.5V	1A, Fixed	Reel	Contact us
	TO-252 3L	LM39100RS-2.5V	1A, Fixed	Reel	Active
	TO-252 3L	LM39100GRS-2.5V	1A, Fixed	Reel	Active
	TO-252 5L	LM39101RS-2.5V	1A, Fixed, Enable	Reel	Active
	TO-252 5L	LM39101GRS-2.5V	1A, Fixed, Enable	Reel	Active
	SOP-8	LM39101D-2.5V	1A, Fixed, Enable	Reel	Active
3.3 V	SOT-223	LM39100S-3.3V	1A, Fixed	Reel	Active
	SOT-223	LM39100GS-3.3V	1A, Fixed	Reel	Contact us
	TO-252 3L	LM39100RS-3.3V	1A, Fixed	Reel	Active
	TO-252 3L	LM39100GRS-3.3V	1A, Fixed	Reel	Active
	TO-252 5L	LM39101RS-3.3V	1A, Fixed, Enable	Reel	Active
	TO-252 5L	LM39101GRS-3.3V	1A, Fixed, Enable	Reel	Active
	SOP-8	LM39101D-3.3V	1A, Fixed, Enable	Reel	Active


1A Low-Voltage Low-Dropout Regulator LM39100/39101/39102

Ordering Information


V _{OUT}	Package	Order No.	Description	Supplied As	Status
5.0 V	SOT-223	LM39100S-5.0V	1A, Fixed	Reel	Active
	SOT-223	LM39100GS-5.0V	1A, Fixed	Reel	Contact us
	TO-252 3L	LM39100RS-5.0V	1A, Fixed	Reel	Active
	TO-252 3L	LM39100GRS-5.0V	1A, Fixed	Reel	Active
	TO-252 5L	LM39101RS-5.0V	1A, Fixed, Enable	Reel	Active
	TO-252 5L	LM39101GRS-5.0V	1A, Fixed, Enable	Reel	Active
	SOP-8	LM39101D-5.0V	1A, Fixed, Enable	Reel	Active
ADJ	TO-252 5L	LM39102RS	1A, Adjustable, Enable	Reel	Active
	TO-252 5L	LM39102GRS	1A, Adjustable, Enable	Reel	Active
	SOP-8	LM39102D	1A, Adjustable, Enable	Reel	Active




PIN CONFIGURATION




SOP-8



SOT-223



TO-252 3L



TO-252 5L

PIN DESCRIPTION


Pin No.	SOT-223 & TO-252 3L (for 39100)	
	Name	Function
1	VIN	Input Supply
2	GND	Ground
3	VOUT	Output Voltage

Pin No.	TO-252 5L (for 39101/2)		SOP-8 (for 39101/2)	
	Name	Function	Name	Function
1	EN	Chip Enable	EN	Chip Enable
2	VIN	Input Supply	VIN	Input Supply
3	GND	Ground	VOUT	Output Voltage
4	VOUT	Output Voltage	FLG / ADJ	Error Flag Output or Output Adjust
5	FLG / ADJ	Error Flag Output or Output Adjust	GND	Ground
6 / 7 / 8	-	-	GND	Ground


1A Low-Voltage Low-Dropout Regulator

LM39100/39101/39102


TYPICAL APPLICATION



2.5V / 1A Regulator



2.5V / 1A Regulator with Error Flag



1.5V / 1A Adjustable Regulator

ELECTRICAL CHARACTERISTICS

$V_{IN} = V_{OUT} + 1V$; $V_{EN} = 2.25V$; $T_J = 25^\circ C$, **bold** values indicate $-40^\circ C \leq T_J \leq +125^\circ C$; unless noted

Symbol	Parameters	Condition	Min.	Typ.	Max.	Unit
V_{OUT}	Output Voltage	10mA	-1		1	%
		$10mA \leq I_{OUT} \leq 1A$, $V_{OUT} + 1V \leq V_{IN} \leq 8V$	-2		2	%
	Line Regulation	$I_{OUT} = 10mA$, $V_{OUT} + 1V \leq V_{IN} \leq 16V$		0.06	0.5	%
	Load Regulation	$V_{IN} = V_{OUT} + 1V$, $10mA \leq I_{OUT} \leq 1A$		0.2	1	%
$\Delta V_{OUT}/\Delta T$	Output Voltage Temp. Coefficient (Note 4)			40	100	ppm/°C
V_{DO}	Dropout Voltage (Note 5)	$I_{OUT} = 100mA$, $\Delta V_{OUT} = -1\%$		150	200 250	mV mV
		$I_{OUT} = 500mA$, $\Delta V_{OUT} = -1\%$		275		mV
		$I_{OUT} = 750mA$, $\Delta V_{OUT} = -1\%$		330	500	mV
		$I_{OUT} = 1A$, $\Delta V_{OUT} = -1\%$		410	550 630	mV mV
I_{GND}	Ground Current (Note 6)	$I_{OUT} = 100mA$, $V_{IN} = V_{OUT} + 1V$		700		μA
		$I_{OUT} = 500mA$, $V_{IN} = V_{OUT} + 1V$		4		mA
		$I_{OUT} = 750mA$, $V_{IN} = V_{OUT} + 1V$		7		mA
$I_{OUT(lim)}$	Current Limit	$V_{OUT} = 0V$, $V_{IN} = V_{OUT} + 1V$	1.3	2.5	3.5	A

Enable Input

V_{EN}	Enable Input Voltage	logic low (off)			0.8	V
		logic high (on)	2.25			V
I_{EN}	Enable Input Current	$V_{EN} = 2.25V$	1	15	30 75	μA μA
		$V_{EN} = 0.8V$			2 4	μA μA
T_{EN}	Delay time to Nominal Output Voltage (Note 7)	$I_{OUT} = 10mA$, $V_{IN} = V_{OUT} + 1V$, $V_{EN} = 0V$ to V_{IN}		50	500	μs
		$I_{OUT} = 500mA$, $V_{IN} = V_{OUT} + 1V$, $V_{EN} = 0V$ to V_{IN}		250	2000	
		$I_{OUT} = 1.0A$, $V_{IN} = V_{OUT} + 1V$, $V_{EN} = 0V$ to V_{IN}		350	3000	

Flag Output

$I_{FLG(leak)}$	Output Leakage Current	$V_{OH} = 16V$		0.01	1 2	μA μA
				240	300 400	mV mV
$V_{FLG(do)}$	Output Low Voltage (Note 8)	$V_{IN} = 0.9 \cdot V_{OUT\ NOMINAL}$, $I_{OL} = 250\mu A$				
V_{FLG}	Low Threshold	% of V_{OUT}	93			%
	High Threshold	% of V_{OUT}			99.2	%
	Hysteresis			1		%

LM39102 Only

	Reference Voltage		1.228 1.215	1.24	1.252 1.265	V V
		(Note 9)	1.203		1.277	V
	Adjust Pin Bias Current			40	80 120	nA nA
	Reference Voltage Temp. Coefficient (Note 4)			20		ppm/ °C
	Adjust Pin Bias Current Temp. Coefficient			0.1	99.2	nA/ °C

Note 1. Exceeding the absolute maximum ratings may damage the device.

Note 2. The device is not guaranteed to function outside its operating rating.

Note 3. $PD (max) = (T_{J(max)} - T_A) \div \theta_{JA}$, where θ_{JA} - junction-to-ambient thermal resistance.

Note 4. Output voltage temperature coefficient is $\Delta V_{OUT} (worst\ case) \div (T_{J(max)} - T_{J(min)})$ where $T_{J(max)}$ is +125°C and $T_{J(min)}$ is 0°C.

Note 5. $V_{DO} = V_{IN} - V_{OUT}$ when V_{OUT} decreases to 99% of its nominal output voltage with $V_{IN} = V_{OUT} + 1V$. For output voltages below 2.25V, dropout voltage is the input-to-output voltage differential with the minimum input voltage being 2.25V. Minimum input operating voltage is 2.25V.










Note 6. I_{GND} is the quiescent current. $I_{IN} = I_{GND} + I_{OUT}$.

Note 7. Delay time is measured after $V_{EN} = V_{IN}$. $C_{IN} = C_{OUT} = 10\mu F$.













Note 8. For adjustable device and fixed device with $V_{OUT} \geq 2.5V$

Note 9. $V_{REF} \leq V_{OUT} \leq (V_{IN} - 1V)$, $2.25V \leq V_{IN} \leq 16V$, $10mA \leq I_L \leq 1A$.

TYPICAL OPERATING CHARACTERISTICS



TYPICAL OPERATING CHARACTERISTICS



APPLICATION INFORMATION

The **LM39100/1/2** is a high-performance low-dropout voltage regulator suitable for moderate to high-current voltage regulator applications. Its 630mV dropout voltage at full load and over temperature makes it especially valuable in battery-powered systems and as high-efficiency noise filters in post-regulator applications. Unlike older NPN-pass transistor designs, where the minimum dropout voltage is limited by the base-to-emitter voltage drop and collector-to-emitter saturation voltage, dropout performance of the PNP output of these devices is limited only by the low VCE saturation voltage. A trade-off for the low dropout voltage is a varying base drive requirement.

The LM39100/1/2 regulator is fully protected from damage due to fault conditions. Linear current limiting is provided. Output current during overload conditions is constant. Thermal shutdown disables the device when the die temperature exceeds the maximum safe operating temperature. Transient protection allows device (and load) survival even when the input voltage spikes above and below nominal. The output structure of these regulators allows voltages in excess of the desired output voltage to be applied without reverse current flow.

Output Capacitor

The LM39100/1/2 requires an output capacitor to maintain stability and improve transient response. Proper capacitor selection is important to ensure proper operation. The LM39100/1/2 output capacitor selection is dependent upon the ESR (equivalent series resistance) of the output capacitor to maintain stability. When the output capacitor is 10 μ F or greater, the output capacitor should have an ESR less than 2 Ω . This will improve transient response as well as promote stability. Ultra-low ESR capacitors (<100m Ω), such as ceramic chip capacitors, may promote the instability. These very low ESR levels may cause an oscillation and/or underdamped transient response. A low ESR solid tantalum capacitor works extremely well and provides a good transient response and the stability over the temperature range. Aluminum electrolytes can also be used, as long as the capacitor ESR is <2 Ω . The value of the output capacitor can be increased without limit. Higher capacitance values help one to improve transient response and ripple rejection and reduce an output noise.

Input Capacitor

An input capacitor of 1 μ F or greater is recommended when the device is more than 4 inches away from the bulk ac supply capacitance or when the supply is a battery. In the case of ceramic chip capacitor, 10 μ F capacitance is recommended. Larger values will help to improve ripple rejection by bypassing the input to the regulator, further improving the integrity of the output voltage.

Error Flag

The LM39101 features an error flag (FLG), which monitors the output voltage and signals an error condition when this voltage drops 5% below its expected value. The error flag is an open-collector output that pulls low under fault conditions and may sink up to 10mA. Low output voltage signifies a number of possible problems, including an over current fault (the device is in current limit) or low input voltage. The flag output is inoperative during over temperature conditions. A pull-up resistor from FLG to either V_{IN} or V_{OUT} is required for proper operation. For information regarding the minimum and maximum values of pull-up resistance, refer to the graph in the typical characteristics section of the data sheet.

Enable Input

The LM39101 and LM39102 versions feature an active-high enable input (EN) that allows on-off control of the regulator. Current drain reduces to “zero” when the device is shutdown, with only micro amperes of leakage current. The EN input has TTL/CMOS compatible thresholds for simple logic interfacing. EN may be directly tied to V_{IN} and pulled up to the maximum supply voltage

Transient Response and 3.3V to 2.5V or 2.5V to 1.8V Conversion

The LM39100/1/2 has excellent transient response to variations in input voltage and load current. The device has been designed to respond quickly to load current variations and input voltage variations. Large output capacitors are not required to obtain this performance. A standard 10 μ F output capacitor, preferably tantalum, is all that is required. Larger values help to improve performance even further.

By virtue of its low-dropout voltage, this device does not saturate into dropout as readily as similar NPN-based de-signs. When converting from 3.3V to 2.5V or 2.5V to 1.8V, the NPN based regulators are already operating in dropout, with typical dropout requirements of 1.2V or greater. To convert down to 2.5V or 1.8V without operating in dropout, NPN-based regulators require an input voltage of 3.7V at the very least. The LM39100 regulator will provide excellent performance with an input as low as 3.0V or 2.5V respectively. This gives the PNP based regulators a distinct advantage over older, NPN based linear regulators.

Minimum Load Current

The LM39100/1/2 regulator is specified between finite loads. If the output current is too small, leakage currents dominate and the output voltage rises. A 10mA minimum load current is necessary for proper regulation.

Adjustable Regulator Design

The LM39102 allows programming the output voltage any-where between 1.24V and the 16V maximum operating rating of the family. Two resistors are used. Resistors can be quite large, up to 1M Ω , because of the very high input impedance and low bias current of the sense comparator: The resistor values are calculated by : $R1=R2(V_{out}/1.240-1)$ Where V_{out} is the desired output voltage. Figure 1 shows component definition. Applications with widely varying load currents may scale the resistors to draw the minimum load current required for proper operation (see below). The current consumed by feedback resistors R1 and R2 is calculated by: $I_{res} = V_{out} / (R1+ R2)$.




Figure 1. Adjustable Regulator with Resistors

Maximum Output Current Capability

The LM39100/1/2 can deliver a continuous current of 1A over the full operating junction temperature range. However, the output current is limited by the restriction of power dissipation which differs from packages. A

1A Low-Voltage Low-Dropout Regulator LM39100/39101/39102

heat sink may be required depending on the maximum power dissipation and maximum ambient temperature of application. With respect to the applied package, the maximum output current of 1A may be still undeliverable due to the restriction of the power dissipation of LM39100/1/2. Under all possible conditions, the junction temperature must be within the range specified under operating conditions. The temperatures over the device are given by:

$$T_C = T_A + P_D \times \theta_{CA} / \quad T_J = T_C + P_D \times \theta_{JC} / \quad T_J = T_A + P_D \times \theta_{JA}$$

Where T_J is the junction temperature, T_C is the case temperature, T_A is the ambient temperature, P_D is the total power dissipation of the device, θ_{CA} is the thermal resistance of case-to-ambient, θ_{JC} is the thermal resistance of junction-to-case, and θ_{JA} is the thermal resistance of junction to ambient. The total power dissipation of the device is given by:

$$\begin{aligned} P_D &= P_{IN} - P_{OUT} = (V_{IN} \times I_{IN}) - (V_{OUT} \times I_{OUT}) \\ &= (V_{IN} \times (I_{OUT} + I_{GND})) - (V_{OUT} \times I_{OUT}) = (V_{IN} - V_{OUT}) \times I_{OUT} + V_{IN} \times I_{GND} \end{aligned}$$

Where I_{GND} is the operating ground current of the device which is specified at the Electrical Characteristics. The maximum allowable temperature rise (T_{Rmax}) depends on the maximum ambient temperature (T_{Amax}) of the application, and the maximum allowable junction temperature (T_{Jmax}):

$$T_{Rmax} = T_{Jmax} - T_{Amax}$$

The maximum allowable value for junction-to-ambient thermal resistance, θ_{JA} , can be calculated using the formula:

$$\theta_{JA} = T_{Rmax} / P_D = (T_{Jmax} - T_{Amax}) / P_D$$


LM39100/1/2 is available in SOT-223, TO-252, and SOP-8 package. The thermal resistance depends on amount of copper area or heat sink, and on air flow. If the maximum allowable value of θ_{JA} calculated above is over 115°C/W for SOT-223 package, 95°C/W for TO-252 package, 130°C/W for SOP-8 package, no heat sink is needed since the package can dissipate enough heat to satisfy these requirements. If the value for allowable θ_{JA} falls near or below these limits, a heat sink or proper area of copper plane is required. In summary, the absolute maximum ratings of thermal resistances are as follow:

Absolute Maximum Ratings of Thermal Resistance


Characteristic	Symbol	Rating	Unit
Thermal Resistance Junction-To-Ambient / SOT-223	$\theta_{JA-SOT-223}$	115	°C/W
Thermal Resistance Junction-To-Ambient / TO-252	$\theta_{JA-TO-252}$	95	°C/W
Thermal Resistance Junction-To-Ambient / SOP-8	$\theta_{JA-SOP-8}$	130	°C/W

No heat sink / No air flow / No adjacent heat source / 20 mm² copper area. ($T_A=25^\circ\text{C}$)

Power Dissipation(Pd)
vs. Copper Area (SOP-8)



Thermal Resistance(θJA)
vs. Copper Area (SOP-8)




FEATURES

- Output Current up to 1.5A
- Internal Thermal Overload Protection
- Internal Short-Circuit Current Limiting
- Output Transistor Safe-Area Compensation
- Output Voltage of 5V, 6V, 8V, 9V, 12V, 15V, 18V, 20V, and 24V
- Available in SOT-223, TO-252, TO-263, TO-220 and TO-220F Packages

DESCRIPTION

The series of fixed-Positive voltage monolithic integrated circuit voltage regulator is designed to complement LM78xx series in a wide range of applications. These applications include on-card regulation for elimination of noise and distribution problems associated with single-point regulation.

Each of these regulators can deliver up to 1.5A of output current. The internal limiting and thermal shutdown features of these regulators make them essentially immune to overload. In addition to use as fixed-voltage regulators, these devices can be used with external components to obtain adjustable output voltages and current and also as the power pass element in precision regulators.



ORDERING INFORMATION

Device	Package
LM78xxS	SOT-223-3L
LM78xxRS	TO-252-3L
LM78xxR	TO-263-3L
LM78xxT	TO-220-3L
LM78xxTP	TO-220F-3L

xx: Output Voltage

ABSOLUTE MAXIMUM RATINGS (Note 1)





CHARACTERISTIC		SYMBOL	MIN	MAX	UNIT
Input Voltage	$V_{OUT} = 5V \text{ to } 18V$	V_{IN}	-	35	V
	$V_{OUT} = 20V \text{ and } 24V$		-	40	
Maximum Junction Temperature		T_J	-40	125	°C
Storage Temperature		T_{STG}	-65	150	°C

Note 1. Stresses beyond those listed under *Absolute Maximum Ratings* may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions* is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

ORDERING INFORMATION

VOUT	Package	Order No.	Description	Supplied As	Status
5.0V	SOT-223-3L	LM7805S	1.5A, Fixed	Tape & Reel	Active
	TO-252-3L	LM7805RS	1.5A, Fixed	Tape & Reel	Active
	TO-263-3L	LM7805R	1.5A, Fixed	Tape & Reel	Active
	TO-220-3L	LM7805T	1.5A, Fixed	Tube	Active
	TO-220F-3L	LM7805TP	1.5A, Fixed	Tube	Active
6.0V	TO-252-3L	LM7806RS	1.5A, Fixed	Tape & Reel	Contact us
	TO-263-3L	LM7806R	1.5A, Fixed	Tape & Reel	Contact us
	TO-220-3L	LM7806T	1.5A, Fixed	Tube	Active
	TO-220F-3L	LM7806TP	1.5A, Fixed	Tube	Contact us
8.0V	TO-252-3L	LM7808RS	1.5A, Fixed	Tape & Reel	Contact us
	TO-263-3L	LM7808R	1.5A, Fixed	Tape & Reel	Contact us
	TO-220-3L	LM7808T	1.5A, Fixed	Tube	Contact us
	TO-220F-3L	LM7808TP	1.5A, Fixed	Tube	Contact us
9.0V	TO-252-3L	LM7809RS	1.5A, Fixed	Tape & Reel	Contact us
	TO-263-3L	LM7809R	1.5A, Fixed	Tape & Reel	Contact us
	TO-220-3L	LM7809T	1.5A, Fixed	Tube	Active
	TO-220F-3L	LM7809TP	1.5A, Fixed	Tube	Contact us
12V	TO-252-3L	LM7812RS	1.5A, Fixed	Tape & Reel	Contact us
	TO-263-3L	LM7812R	1.5A, Fixed	Tape & Reel	Contact us
	TO-220-3L	LM7812T	1.5A, Fixed	Tube	Active
	TO-220F-3L	LM7812TP	1.5A, Fixed	Tube	Active
15V	TO-252-3L	LM7815RS	1.5A, Fixed	Tape & Reel	Contact us
	TO-263-3L	LM7815R	1.5A, Fixed	Tape & Reel	Contact us
	TO-220-3L	LM7815T	1.5A, Fixed	Tube	Active
	TO-220F-3L	LM7815TP	1.5A, Fixed	Tube	Contact us
18V	TO-252-3L	LM7818RS	1.5A, Fixed	Tape & Reel	Contact us
	TO-263-3L	LM7818R	1.5A, Fixed	Tape & Reel	Contact us
	TO-220-3L	LM7818T	1.5A, Fixed	Tube	Contact us
	TO-220F-3L	LM7818TP	1.5A, Fixed	Tube	Contact us
20V	TO-252-3L	LM7820RS	1.5A, Fixed	Tape & Reel	Contact us
	TO-263-3L	LM7820R	1.5A, Fixed	Tape & Reel	Contact us
	TO-220-3L	LM7820T	1.5A, Fixed	Tube	Contact us
	TO-220F-3L	LM7820TP	1.5A, Fixed	Tube	Contact us
24V	TO-252-3L	LM7824RS	1.5A, Fixed	Tape & Reel	Contact us
	TO-263-3L	LM7824R	1.5A, Fixed	Tape & Reel	Contact us
	TO-220-3L	LM7824T	1.5A, Fixed	Tube	Active
	TO-220F-3L	LM7824TP	1.5A, Fixed	Tube	Contact us


PIN CONFIGURATION

			
SOT-223	TO-252	TO-263	TO-220 / TO-220F

PIN DESCRIPTION

Pin No.				Pin Name	Pin Function
TO-252	TO-263	TO-220	TO-220F		
1	1	1	1	INPUT	Input Voltage
2	2	2	2	GND	Ground (Common)
3	3	3	3	OUTPUT	Output Voltage
TAB	TAB	TAB	TAB	TAB	<p>Connect to GND. Attached to heatsink for thermal relief for TO-220 package or put a copper plane connected to this pin as a thermal relief for TO-263 package.</p> <p>No Connection, Electrically Isolated for TO-220F Package</p>

TYPICAL APPLICATION CIRCUITS



- * C_{IN} required for stability. Value given may be increased.
- ** C_{OUT} may be used to improve the transient response of the regulator. It should be located as close as possible for the regulator. Value given may be increased.

ELECTRICAL CHARACTERISTICS: LM7805

Specifications with standard type face are for $T_J = 25^\circ\text{C}$, and those with **boldface type** apply over $T_J = 0^\circ\text{C}$ to 125°C . Conditions are $V_{IN} = 10\text{V}$, $I_{OUT} = 500\text{mA}$, $C_{IN} = 0.33\mu\text{F}$, $C_{OUT} = 0.1\mu\text{F}$, unless otherwise noted.

PARAMETER	SYMBOL	TEST CONDITIONS (Note 3)	MIN	TYP	MAX	UNIT
Output Voltage (Note 4)	V_{OUT}		4.80	5.0	5.20	V
		$7\text{V} \leq V_{IN} \leq 20\text{V}$, $5.0\text{mA} \leq I_{OUT} \leq 1.0\text{A}$	4.75	5.0	5.25	
Line Regulation	ΔV_{LINE}	$7\text{V} \leq V_{IN} \leq 25\text{V}$	-	-	100	mV
		$8.0\text{V} \leq V_{IN} \leq 12\text{V}$	-	-	50	
Load Regulation	ΔV_{LOAD}	$5.0\text{mA} \leq I_{OUT} \leq 1.5\text{A}$	-	-	100	mV
		$0.25\text{A} \leq I_{OUT} \leq 0.75\text{A}$	-	-	50	
Dropout Voltage	V_D	$I_{OUT} = 1.0\text{A}$	-	2.0	-	V
Bias Current	I_B		-	-	8.0	mA
Bias Current Change	ΔI_B	$7\text{V} \leq V_{IN} \leq 25\text{V}$	-	-	1.3	mA
		$5.0\text{mA} \leq I_{OUT} \leq 1.0\text{A}$	-	-	0.5	

Note 3. Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible. Thermal effects must be taken into account separately.

Note 4. This specification applies only for DC power dissipation permitted by the *Absolute Maximum Ratings*.

ELECTRICAL CHARACTERISTICS: LM7806

Specifications with standard type face are for $T_J = 25^\circ\text{C}$, and those with **boldface type** apply over $T_J = 0^\circ\text{C}$ to 125°C . Conditions are $V_{IN} = 11\text{V}$, $I_{OUT} = 500\text{mA}$, $C_{IN} = 0.33\mu\text{F}$, $C_{OUT} = 0.1\mu\text{F}$, unless otherwise noted.

PARAMETER	SYMBOL	TEST CONDITIONS (Note 3)	MIN	TYP	MAX	UNIT
Output Voltage (Note 4)	V_{OUT}		5.76	6.0	6.24	V
		$8\text{V} \leq V_{IN} \leq 21\text{V}$, $5.0\text{mA} \leq I_{OUT} \leq 1.0\text{A}$	5.70	6.0	6.30	
Line Regulation	ΔV_{LINE}	$8\text{V} \leq V_{IN} \leq 25\text{V}$	-	-	120	mV
		$9\text{V} \leq V_{IN} \leq 13\text{V}$	-	-	60	
Load Regulation	ΔV_{LOAD}	$5.0\text{mA} \leq I_{OUT} \leq 1.5\text{A}$	-	-	120	mV
		$0.25\text{A} \leq I_{OUT} \leq 0.75\text{A}$	-	-	60	
Dropout Voltage	V_D	$I_{OUT} = 1.0\text{A}$	-	2.0	-	V
Bias Current	I_B		-	-	8.0	mA
Bias Current Change	ΔI_B	$8.0\text{V} \leq V_{IN} \leq 25\text{V}$	-	-	1.3	mA
		$5.0\text{mA} \leq I_{OUT} \leq 1.0\text{A}$	-	-	0.5	

Note 3. Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible. Thermal effects must be taken into account separately.

Note 4. This specification applies only for DC power dissipation permitted by the *Absolute Maximum Ratings*.

ELECTRICAL CHARACTERISTICS: LM7808

Specifications with standard type face are for $T_J = 25^\circ\text{C}$, and those with **boldface type** apply over $T_J = 0^\circ\text{C}$ to 125°C . Conditions are $V_{IN} = 14\text{V}$, $I_{OUT} = 500\text{mA}$, $C_{IN} = 0.33\mu\text{F}$, $C_{OUT} = 0.1\mu\text{F}$, unless otherwise noted.

PARAMETER	SYMBOL	TEST CONDITIONS (Note 3)	MIN	TYP	MAX	UNIT
Output Voltage (Note 4)	V_{OUT}		7.7	8.0	8.3	V
		$10.5\text{V} \leq V_{IN} \leq 23\text{V}$, $5.0\text{mA} \leq I_{OUT} \leq 1.0\text{A}$	7.6	8.0	8.4	
Line Regulation	ΔV_{LINE}	$10.5\text{V} \leq V_{IN} \leq 25\text{V}$	-	-	160	mV
		$11\text{V} \leq V_{IN} \leq 17\text{V}$	-	-	80	
Load Regulation	ΔV_{LOAD}	$5.0\text{mA} \leq I_{OUT} \leq 1.5\text{A}$	-	-	160	mV
		$0.25\text{A} \leq I_{OUT} \leq 0.75\text{A}$	-	-	80	
Dropout Voltage	V_D	$I_{OUT} = 1.0\text{A}$	-	2.0	-	V
Bias Current	I_B		-	-	8.0	mA
Bias Current Change	ΔI_B	$10.5\text{V} \leq V_{IN} \leq 25\text{V}$	-	-	1.3	mA
		$5.0\text{mA} \leq I_{OUT} \leq 1.0\text{A}$	-	-	0.5	

Note 3. Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible. Thermal effects must be taken into account separately.

Note 4. This specification applies only for DC power dissipation permitted by the *Absolute Maximum Ratings*.

ELECTRICAL CHARACTERISTICS: LM7809

Specifications with standard type face are for $T_J = 25^\circ\text{C}$, and those with **boldface type** apply over $T_J = 0^\circ\text{C}$ to 125°C . Conditions are $V_{IN} = 15\text{V}$, $I_{OUT} = 500\text{mA}$, $C_{IN} = 0.33\mu\text{F}$, $C_{OUT} = 0.1\mu\text{F}$, unless otherwise noted.

PARAMETER	SYMBOL	TEST CONDITIONS (Note 3)	MIN	TYP	MAX	UNIT
Output Voltage (Note 4)	V_{OUT}		8.64	9.0	9.36	V
		$11.5\text{V} \leq V_{IN} \leq 24\text{V}$, $5.0\text{mA} \leq I_{OUT} \leq 1.0\text{A}$	8.55	9.0	9.45	
Line Regulation	ΔV_{LINE}	$11.5\text{V} \leq V_{IN} \leq 26\text{V}$	-	-	180	mV
		$11.5\text{V} \leq V_{IN} \leq 17\text{V}$	-	-	90	
Load Regulation	ΔV_{LOAD}	$5.0\text{mA} \leq I_{OUT} \leq 1.5\text{A}$	-	-	180	mV
		$0.25\text{A} \leq I_{OUT} \leq 0.75\text{A}$	-	-	90	
Dropout Voltage	V_D	$I_{OUT} = 1.0\text{A}$	-	2.0	-	V
Bias Current	I_B		-	-	8.0	mA
Bias Current Change	ΔI_B	$11.5\text{V} \leq V_{IN} \leq 26\text{V}$	-	-	1.3	mA
		$5.0\text{mA} \leq I_{OUT} \leq 1.0\text{A}$	-	-	0.5	

Note 3. Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible. Thermal effects must be taken into account separately.

Note 4. This specification applies only for DC power dissipation permitted by the *Absolute Maximum Ratings*.

ELECTRICAL CHARACTERISTICS: LM7812

Specifications with standard type face are for $T_J = 25^\circ\text{C}$, and those with **boldface type** apply over $T_J = 0^\circ\text{C}$ to 125°C . Conditions are $V_{IN} = 19\text{V}$, $I_{OUT} = 500\text{mA}$, $C_{IN} = 0.33\mu\text{F}$, $C_{OUT} = 0.1\mu\text{F}$, unless otherwise noted.

PARAMETER	SYMBOL	TEST CONDITIONS (Note 3)	MIN	TYP	MAX	UNIT
Output Voltage (Note 4)	V_{OUT}		11.5	12	12.5	V
		$14.5\text{V} \leq V_{IN} \leq 27\text{V}$, $5.0\text{mA} \leq I_{OUT} \leq 1.0\text{A}$	11.4	12	12.6	
Line Regulation	ΔV_{LINE}	$14.5\text{V} \leq V_{IN} \leq 30\text{V}$	-	-	240	mV
		$16\text{V} \leq V_{IN} \leq 22\text{V}$	-	-	120	
Load Regulation	ΔV_{LOAD}	$5.0\text{mA} \leq I_{OUT} \leq 1.5\text{A}$	-	-	240	mV
		$0.25\text{A} \leq I_{OUT} \leq 0.75\text{A}$	-	-	120	
Dropout Voltage	V_D	$I_{OUT} = 1.0\text{A}$	-	2.0	-	V
Bias Current	I_B		-	-	8.0	mA
Bias Current Change	ΔI_B	$14.5\text{V} \leq V_{IN} \leq 30\text{V}$	-	-	1.3	mA
		$5.0\text{mA} \leq I_{OUT} \leq 1.0\text{A}$	-	-	0.5	

Note 3. Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible. Thermal effects must be taken into account separately.

Note 4. This specification applies only for DC power dissipation permitted by the *Absolute Maximum Ratings*.

ELECTRICAL CHARACTERISTICS: LM7815

Specifications with standard type face are for $T_J = 25^\circ\text{C}$, and those with **boldface type** apply over $T_J = 0^\circ\text{C}$ to 125°C . Conditions are $V_{IN} = 23\text{V}$, $I_{OUT} = 500\text{mA}$, $C_{IN} = 0.33\mu\text{F}$, $C_{OUT} = 0.1\mu\text{F}$, unless otherwise noted.

PARAMETER	SYMBOL	TEST CONDITIONS (Note 3)	MIN	TYP	MAX	UNIT
Output Voltage (Note 4)	V_{OUT}		14.4	15	15.6	V
		$17.5\text{V} \leq V_{IN} \leq 30\text{V}$, $5.0\text{mA} \leq I_{OUT} \leq 1.0\text{A}$	14.25	15	15.75	
Line Regulation	ΔV_{LINE}	$17.5\text{V} \leq V_{IN} \leq 30\text{V}$	-	-	300	mV
		$20\text{V} \leq V_{IN} \leq 26\text{V}$	-	-	150	
Load Regulation	ΔV_{LOAD}	$5.0\text{mA} \leq I_{OUT} \leq 1.5\text{A}$	-	-	300	mV
		$0.25\text{A} \leq I_{OUT} \leq 0.75\text{A}$	-	-	150	
Dropout Voltage	V_D	$I_{OUT} = 1.0\text{A}$	-	2.0	-	V
Bias Current	I_B		-	-	8.0	mA
Bias Current Change	ΔI_B	$17.5\text{V} \leq V_{IN} \leq 30\text{V}$	-	-	1.3	mA
		$5.0\text{mA} \leq I_{OUT} \leq 1.0\text{A}$	-	-	0.5	

Note 3. Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible. Thermal effects must be taken into account separately.

Note 4. This specification applies only for DC power dissipation permitted by the *Absolute Maximum Ratings*.

ELECTRICAL CHARACTERISTICS: LM7824

Specifications with standard type face are for $T_J = 25^\circ\text{C}$, and those with **boldface type** apply over $T_J = 0^\circ\text{C}$ to 125°C . Conditions are $V_{IN} = 33\text{V}$, $I_{OUT} = 500\text{mA}$, $C_{IN} = 0.33\mu\text{F}$, $C_{OUT} = 0.1\mu\text{F}$, unless otherwise noted.

PARAMETER	SYMBOL	TEST CONDITIONS (Note 3)	MIN	TYP	MAX	UNIT
Output Voltage (Note 4)	V_{OUT}		23	24	25	V
		$27\text{V} \leq V_{IN} \leq 38\text{V}$, $5.0\text{mA} \leq I_{OUT} \leq 1.0\text{A}$	22.8	24	25.2	
Line Regulation	ΔV_{LINE}	$27\text{V} \leq V_{IN} \leq 38\text{V}$	-	-	480	mV
		$30\text{V} \leq V_{IN} \leq 36\text{V}$	-	-	240	
Load Regulation	ΔV_{LOAD}	$5.0\text{mA} \leq I_{OUT} \leq 1.5\text{A}$	-	-	480	mV
		$0.25\text{A} \leq I_{OUT} \leq 0.75\text{A}$	-	-	240	
Dropout Voltage	V_D	$I_{OUT} = 1.0\text{A}$	-	2.0	-	V
Bias Current	I_B		-	-	8.0	mA
Bias Current Change	ΔI_B	$27\text{V} \leq V_{IN} \leq 38\text{V}$	-	-	1.3	mA
		$5.0\text{mA} \leq I_{OUT} \leq 1.0\text{A}$	-	-	0.5	

Note 3. Pulse testing techniques are used to maintain the junction temperature as close to the ambient temperature as possible. Thermal effects must be taken into account separately.

Note 4. This specification applies only for DC power dissipation permitted by the *Absolute Maximum Ratings*.

Maximum Output Current Capability

The LM78xx can deliver a continuous current of 3.0A over the full operating junction temperature range. However, the output current is limited by the restriction of power dissipation which differs from packages. A heat sink may be required depending on the maximum power dissipation and maximum ambient temperature of application. With respect to the applied package, the maximum output current of 3.0A may be still undeliverable due to the restriction of the power dissipation of LM78xx. Under all possible conditions, the junction temperature must be within the range specified under operating conditions. The temperatures over the device are given by:

$$T_C = T_A + P_D \times \theta_{CA} \quad / \quad T_J = T_C + P_D \times \theta_{JC} \quad / \quad T_J = T_A + P_D \times \theta_{JA}$$

where T_J is the junction temperature, T_C is the case temperature, T_A is the ambient temperature, P_D is the total power dissipation of the device, θ_{CA} is the thermal resistance of case-to-ambient, θ_{JC} is the thermal resistance of junction-to-case, and θ_{JA} is the thermal resistance of junction to ambient. The total power dissipation of the device is given by:

$$P_D = P_{IN} - P_{OUT} = (V_{IN} \times I_{IN}) - (V_{OUT} \times I_{OUT}) \\ = (V_{IN} \times (I_{OUT} + I_{GND})) - (V_{OUT} \times I_{OUT}) = (V_{IN} - V_{OUT}) \times I_{OUT} + V_{IN} \times I_{GND}$$

where I_{GND} is the operating ground current of the device which is specified at the Electrical Characteristics. The maximum allowable temperature rise (T_{Rmax}) depends on the maximum ambient temperature (T_{Amax}) of the application, and the maximum allowable junction temperature (T_{Jmax}):

$$T_{Rmax} = T_{Jmax} - T_{Amax}$$

The maximum allowable value for junction-to-ambient thermal resistance, θ_{JA} , can be calculated using the formula:

$$\theta_{JA} = T_{Rmax} / P_D = (T_{Jmax} - T_{Amax}) / P_D$$

LM78xx is available in SOP8, SOP8-PP, TO225, TO263 and TO220/TO220F packages. The thermal resistance depends on amount of copper area or heat sink, and on air flow. If the maximum allowable value of θ_{JA} calculated above is over 165°C/W for SOP8 package, over 175°C/W for SOP8-PP package, over 105 °C/W for TO252 package, over 80 °C/W for TO263 package, over 70 °C/W for TO220 package, no heat sink is needed since the package can dissipate enough heat to satisfy these requirements. If the value for allowable θ_{JA} falls near or below these limits, a heat sink or proper area of copper plane is required. In summary, the absolute maximum ratings of thermal resistances are as follow:

Absolute Maximum Ratings of Thermal Resistance

No heat sink / No air flow / No adjacent heat source / $T_A = 25^\circ\text{C}$

Characteristic	Symbol	Rating	Unit
Thermal Resistance Junction-To-Ambient / TO252	$\theta_{JA-SOT223}$	137	°C/W
Thermal Resistance Junction-To-Ambient / TO252	$\theta_{JA-TO252}$	105	°C/W
Thermal Resistance Junction-To-Ambient / TO263	$\theta_{JA-TO263}$	80	°C/W
Thermal Resistance Junction-To-Ambient / TO220	$\theta_{JA-TO220}$	70	°C/W
Thermal Resistance Junction-To-Ambient / TO220F	$\theta_{JA-TO220F}$	T.B.D	°C/W

In case that there is no cooling solution and no heat sink / copper plane area for heat sink, the maximum allowable power dissipation of each package is as follow;

Characteristic	Symbol	Rating	Unit
Maximum Allowable Power Dissipation at $T_A=25^\circ\text{C}$ / SOT223	$P_{DMax-SOT223}$	0.729	W
Maximum Allowable Power Dissipation at $T_A=25^\circ\text{C}$ / TO252	$P_{DMax-TO252}$	0.952	W
Maximum Allowable Power Dissipation at $T_A=25^\circ\text{C}$ / TO263	$P_{DMax-TO263}$	1.250	W
Maximum Allowable Power Dissipation at $T_A=25^\circ\text{C}$ / TO220	$P_{DMax-TO220}$	1.429	W
Maximum Allowable Power Dissipation at $T_A=25^\circ\text{C}$ / TO220F	$P_{DMax-TO220F}$	T.B.D	W

- Please note that above maximum allowable power dissipation is based on the minimum copper plane area which does not exceed the proper footprint of the package. And the ambient temperature is 25°C .

If proper cooling solution such as heat sink, copper plane area, air flow is applied, the maximum allowable power dissipation could be increased. However, if the ambient temperature is increased, the allowable power dissipation would be decreased.

REVISION NOTICE

The description in this datasheet is subject to change without any notice to describe its electrical characteristics properly.