



SUGGESTED PCB LAYOUT
TOP VIEW

NOTES:

- Materials:
Housing: PA6T+30%G.F. UL94V-0 Black.
Cover: PBT+30%G.F. UL94V-0 Black.
Shield: 0.20mm Thickness Copper Alloy Ni Plated
Contact: 0.45mm Dia Phosphor Bronze
Plated 3u" Gold Over Ni
- Jack Cavity Confrms To FCC Rules And Regulations Part 68, Subpart F
- Unspecified Tolerance: .XX ±0.25[0.010]
.X ±0.30[0.012]

RoHS Compliant

X MULTIPLE		CONNECTING THE INFORMATION AGE	
X MULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu Chiu, Taipei, Taiwan 11475		X MULTIPLE USA 1402 Los Angeles Ave., Suite G, Simi Valley, CA 93065	
G/NO:		DWG NO:	
THIS DRAWING IS A CONTROLLED DOCUMENT.		XRJD-S-24-8-8-0-801	
TITLE: Stacked RJ45 Connectors, W/O LED, 8P,8C, Shielded, Thru Hole.		DRAWN: RUNES	
PART NO: XRJD-S-24-8-8-0-801		CHKD: JEFF	
UNIT mm[inch]		SHEET 1 of 1	
REV B		DATE: Feb.22,06	