



NOTES:

- Materials:
Housing: PA6T+30%G.F. UL94V-0 Black.
Cover: PBT+30%G.F. UL94V-0 Black.
Shield: 0.20mm Thickness Copper Alloy Ni Plated
Contact: 0.45mm Dia Phosphor Bronze
Plated 3u" Gold Over Ni
- Jack Cavity Confrms To FCC Rules And Regulations Part 68, Subpart F
- Unspecified Tolerance: .XX ±0.25[0.010]
.X ±0.30[0.012]

PCB LAYOUT

| | | | | |
|---|------------------------|--|--------------------------------|-----------------------------------|
| <h1 style="margin: 0;">X MULTIPLE</h1> | | | CONNECTING THE INFORMATION AGE | |
| X MULTIPLE ASIA 4F, No. 347, Yang Guang St., Neihu Chiu, Taipei, Taiwan 11475 | | X MULTIPLE USA 543 Country Club Drive #B 128 Simi Valley, CA 93065 | | CUSTOMER/NO: PJ-DB-0808-FANG-2 |
| THIS DRAWING IS A CONTROLLED DOCUMENT. | | | | |
| TITLE: Stacked RJ45 Connectors, W/D LED, 8P, 8C, Shielded, Thru Hole. | | DVG NO: XRJD-S-28-8-8-0-801 | | DRAWN: ANNIE |
| PART NO: XRJD-S-28-8-8-0-801 | | CHKD: JEFF | | DATE: 08/12/04 |
| | DIMENSIONS mm[inch] | SHEET 1 of 1 | REV 01 | |