


SUGGESTED PCB LAYOUT
TOP VIEW

DIMENSIONAL TOLERANCE: .XX ±0.08[0.003]

NOTES:

- MATERIALS:**
HOUSING: HIGH TEMP. THERMOPLASTIC, PBT, UL 94V-0, BLACK
CONTACTS: T=0.35 mm PHOSPHOR BORNEZE, 50µ" NICKEL UNDERPLATE ON ALL AREA, 100µ" TIN ON TERMINATION END, 15µ" GOLD ON CONTACT AREA.
SHIELD: T=0.25 mm COPPER ZINC ALLOY PLATED WITH NICKEL.
- OPERATING TEMPERATURE:** -40°C ~ +85°C
- JACK CAVITY CONFORMS TO FCC RULES AND REGULATIONS PART 68, SUBPART F**
- UNSPECIFIED TOLERANCE:** .XX ±0.25[0.010]
.X ±0.30[0.012]



LED SCHEMATIC

RoHS Compliant

Kinnex A

KINNEXA, INC.
4F, No. 347, Yang Guang St.,
Neihu, Taipei, Taiwan 11491

THIS DRAWING IS A CONTROLLED DOCUMENT.			DWG NO: XRJM-S-04-8-8-4
TITLE: RJ45 Connectors, W/LED, 8P,8C, Shielded, Thru-Hole			DRAWN: NINA
PART NO: XRJM-S-04-8-8-4			CHKD: TARA
UNIT mm[inch]	SHEET 1 of 1	REV D	DATE: Nov,09,12