



10.3 x 10.3 x 4.0 mm

YC104RT




Test Frequency : 100KHz/250mV (CH-1061)


Inductance : 1.0uH~1000uH

DC Resistance : 0.01Ω~5.5Ω Max (CH-502A)


Packing Quantity : 1000pcs/reel, 7000pcs/ carton




[TOP]



[SIDE]



[BOTTOM]



[PAD]

Part No.	Inductance L (uH)	Test Freq. (kHz)	DC Resistance (Ω)Max	Rated DC Current (A)Max
YC104RT*1R0N	1.0	100	0.010	7.00
YC104RT*2R2N	2.2	100	0.013	6.50
YC104RT*3R3N	3.3	100	0.020	6.30
YC104RT*4R7N	4.7	100	0.025	6.00
YC104RT*6R8M	6.8	100	0.032	5.00
YC104RT*100M	10	100	0.050	4.40
YC104RT*150M	15	100	0.070	3.60
YC104RT*220M	22	100	0.100	2.90
YC104RT*330M	33	100	0.150	2.30
YC104RT*470M	47	100	0.185	2.10
YC104RT*680M	68	100	0.310	1.50
YC104RT*101M	100	100	0.410	1.35
YC104RT*151M	150	100	0.560	1.15
YC104RT*221M	220	100	0.870	0.92
YC104RT*331M	330	100	1.250	0.70
YC104RT*471M	470	100	1.650	0.50
YC104RT*681M	680	100	3.100	0.30
YC104RT*102M	1000	100	5.500	0.20

* Inductance Tolerance : J ±5% , K ±10% , M ±20% , N ±30%