



A	2.0 x No. of Contacts	2.0
B	2.0 x No. of Positions	

2343 2 XX G0 X S U 01

Plastics Height 20=2.0mm 43=4.3mm 46=4.6mm 49=4.9mm 63=6.35mm 72=7.2mm	No. of Rows 1=Single Row 2=Dual Row	No. of Pins Per Row 2X40 2-80	Contact Plating SN: Tin G0: Gold Flash G2: 5U" Gold G3: 10U" Gold G4: 15U" Gold G5: 30U" Gold S0: Gold Flash/Tin Standard: G0	Insulator Material Option A BK-PBT B BK-PA66 C BK-PA6T D BK-PA46 F KB-LCP S Special	Connector Type S= Straight R= Right Angle N= SMT
---	--	--	--	--	--

UNLESS OTHERWISE SPECIFIED TOLERANCE		DRAWN NAME:					
X : ±0.3	X° : ±5°	2.OPF 2xNPin H4.3 W4.5 LCP					
X.X : ±0.2	X.X° : ±1°	SIZE	A4	SCALE	N:1	PROJECT NO.	
X.XX : ±0.1	X.XX° : ±0.5°	REV	A	UNIT	mm	PROJECT	PAGE 1/1
DRAW:	王志钢	CHECKED:		APPROVED:			
DATE:	13/02/12	DATE:		DATE:			