



A	2.54 x No. of Contacts	2.54
B	2.54 x No. of Positions	

SPECIFICATIONS

Current Rating: 3 Amps
 Withstanding Voltage: AC 1000V
 Insulation Resistance: 1000MΩ Min
 Contact Resistance: 20mΩ Max
 Insulator Material: Polyester (UL94V-0)
 Standard: PBT
 Contact Material: Brass
 Contact Plating: Au or SN over 50n" Ni
 Operation Temperature: -40° to +105°
 Max. Processing Temp: 180° C for 30-60 seconds
 (200° C for 10 seconds)

RECOMMEND P. C. BOARD LAYOUT

PCB TOLERANCE: ±0.05 (TOP VIEW)

2285 2 XX G0 X S Y 01

Plastics Height 50=5.0mm 57=5.7mm 68=6.8mm 71=7.1mm 81=8.1mm 85=8.5mm .	No. of Rows 1=Single Row 2=Dual Row	No. of Pins Per Row 2X40 2-80 . . .	Contact Plating SN: Tin G0: Gold Flash G2: 5U" Gold G3: 10U" Gold G4: 15U" Gold G5: 30U" Gold S0: Gold Flash/Tin Standard: G0	Insulator Material Option A BK-PBT B BK-PA66 C BK-PA6T D BK-PA46 F KB-LCP S Special	Connector Type S=Straight R=Right Angle M=SMT . . .
---	--	---	--	--	--

UNLESS OTHERWISE SPECIFIED TOLERANCE		DRAWN NAME:					
X : ±0.3	X° : ±5°	2.54PF 2xNPin H8.5 DIP 带凸					
X.X : ±0.2	X.X° : ±1°	SIZE	A4	SCALE	N:1	PROJECT NO.	
X.XX : ±0.1	X.XX° : ±0.5°	REV	A	UNIT	mm	PROJECT	
DRAW:	吴奇	CHECKED:		APPROVED:		PAGE	1/1
DATE:	25/08/10	DATE:	/ /	DATE:	/ /		