



A	2.0 x No. of Contacts	2.0
B	2.0 x No. of Positions	

SPECIFICATIONS

Current Rating: 1.5 Amps
 Withstanding Voltage: AC 500V
 Insulation Resistance: 1000MΩ Min
 Contact Resistance: 20mΩ Max
 Operation Temperature: -40° to +105°
 Insulator Material: Polyester (UL94V-0)
 Standard: 6T
 Contact Material: Brass
 Contact Plating: Au or SN over 40n" Ni
 Max. Processing Temp: 230° C for 30-60 seconds
 (260° C for 5 seconds)

PIN 0.50X0.20

RECOMMEND P. C. BOARD LAYOUT
 PCB TOLERANCE: ±0.05 (TOP VIEW)

2372 2 XX G0 X R U 01

Plastics Height 20=2.0mm 43=4.3mm 46=4.6mm 49=4.9mm 63=6.35mm 72=7.2mm .	No. of Rows 1=Single Row 2=Dual Row	No. of Pins Per Row 2X40 2-80	Contact Plating SN: Tin G0: Gold Flash G2: 5U" Gold G3: 10U" Gold G4: 15U" Gold G5: 30U" Gold S0: Gold Flash/Tin Standard: G0	Insulator Material Option A BK-PBT B BK-PA66 C BK-PA6T D BK-PA46 F KB-LCP S Special	Connector Type S= Straight R= Right Angle M= SMT
--	--	--	--	--	--

UNLESS OTHERWISE SPECIFIED TOLERANCE		DRAWN NAME:			
X : ±0.3	X° : ±5°	2.0PF 2xNPin H7.2 W4.85 90°			
X.X : ±0.2	X.X° : ±1°	SIZE	A4	SCALE	N:1
X.XX : ±0.1	X.XX° : ±0.5°	REV	A	UNIT	mm
DRAW:	吴奇	CHECKED:		APPROVED:	
DATE:	07/10/10	DATE:		DATE:	